

## PVC-Schlauch mit Gewebeeinlage DIFLEX



Temperatur : -15°C bis +60°C

Ø Innen./Außen. (mm)	Rollen (m)	Biegeradius (mm)	Max. Betriebsdruck (bar)	Farbe	Art. Nr
6 x 12	50	36	15	Blau	<b>DIFLEX 6</b>
8 x 14	50	54	15	Blau	<b>DIFLEX 8</b>
8 x 14	50	54	15	Rot	<b>DIFLEX 8RG</b>
8 x 14	25	54	15	Blau	<b>DIFLEX 8C25</b>
9 x 15	50	66	15	Blau	<b>DIFLEX 9</b>
10 x 16	50	74	15	Blau	<b>DIFLEX 10</b>
10 x 16	50	74	15	Rot	<b>DIFLEX 10RG</b>
10 x 16	25	74	15	Blau	<b>DIFLEX 10C25</b>
12 x 19	50	90	15	Blau	<b>DIFLEX 12</b>
12 x 19	50	90	15	Rot	<b>DIFLEX 12RG</b>
13 x 20	50	101	15	Blau	<b>DIFLEX 13</b>
13 x 20	50	101	15	Rot	<b>DIFLEX 13RG</b>
16 x 22	25	145	10	Blau	<b>DIFLEX 16</b>
19 x 26	25	174	10	Blau	<b>DIFLEX 19</b>
25 x 33	25	260	10	Blau	<b>DIFLEX 25</b>
32 x 42	25	320	11	Durchsichtig	<b>DIFLEX 32</b>
38 x 48	25	420	10	Durchsichtig	<b>DIFLEX 38</b>
50 x 64	25	600	8	Durchsichtig	<b>DIFLEX 50</b>